

# Temperature Extremes Conduit

## ANACONDA SEALTITE® CONDUIT

ANAMET Electrical conduit and fittings protect wiring and cable from

- Extreme temperatures
- Intrusion and wear
- Stress and strain
- Corrosion

**TO  
CONNECT  
AND  
PROTECT**

PHONE: (800) 230-3718  
ANAMETELECTRICAL.COM  
SALES@ANAMETELECTRICAL.COM

**ANAMET Electrical, Inc.** 

ANAMET Electrical is the exclusive manufacturer of ANACONDA SEALTITE® liquid tight wiring conduit and industrial stripwound hose.

# ANACONDA SEALTITE® liquid tight conduit and fittings FIRETECH™ Fire Protective Products

## **XTHF** 1/2 to 1 inch diameter Extreme Temperature, flexible, metallic conduit

### SPECIFICATIONS

- Hot dipped zinc galvanized steel core with silicone jacket
- Color: Gray
- Temp. range: -94°F to +392°F (-70°C to +200°C)
- UV (sunlight) resistant, flame retardant, halogen free

### APPLICATIONS

- Designed for the most extreme temperature applications
- Silicone jacket has superior resistance to chemical breakdown

## **SS-HTUA** 3/8 to 2 inch diameter UL listed, Hot and Cold temperature

### 316 stainless steel



### SPECIFICATIONS

- 316 stainless steel core with liquid tight PVC jacket
- Color: Gray
- Temp. range: -51°F to +221°F (-46°C to +105°C)
- UV (sunlight) and corrosion resistant
- UL Approved #E18917

### APPLICATIONS

- Applications of high and low temperature where a high level of corrosion resistance is required
- Superior wiring protection for petrochemical and offshore industries
- Use a separate grounding conductor or bonding jumper

## **HC** 3/8 to 4 inch diameter Hot and Cold temperature, flexible conduit

### SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray and Black
- Temp. range: -51°F to +221°F (-46°C to +105°C)
- UV (sunlight) and corrosion resistant

### APPLICATIONS

- Applications for high and low temperature where UL and CSA approvals are not required
- Steel and petrochemical industries

## **HTUA-Heavy Duty**

3/8 to 4 inch diameter  
Heavy Duty, High Temperature  
UL Listed and CSA Approved



### SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray
- Temp. range: -51°F to + 221°F (-46°C to +105°C)  
CSA max +167°F (+75°C)
- UV (sunlight) and corrosion resistant
- UL Approved #E18917
- CSA Approved #LL15275
- CSA Certified "Heavy-Duty" 1/2" and up

### APPLICATIONS

- Applications for high and low temperature where UL and CSA approvals are required

## **HGX** 3/8 to 2 inch diameter

Extreme Temperature, Zero Halogen

### SPECIFICATIONS

- Galvanized steel core with liquid tight TPE jacket
- Color: Black
- Temp. range: Static installations -76°F to +302°F (-60°C to +150°C). Dynamic installations at atmospheric pressure rated for -76°F to +221°F (-60°C to +105°C)
- UV (sunlight) and extra corrosion resistant



## **FIRETECH™ SLEEVE/WRAP/TAPE/BLANKET**

- Flexible sleeving for protection of cables from high heat or flame
- Silicone based cover over a knitted fiberglass sleeve
- Superior temperature range for extreme environments
- Abrasion resistant—Ready for the worst environment
- The ultimate protection for harsh industrial applications



RoHS WEEE Compliant