

# CORD GRIPS, STAINLESS STEEL AND NICKEL-PLATED BRASS

## SEALTITE® DOUBLE SEAL CORD GRIPS UL/CSA



### DESCRIPTION

- Two clamping seals are included with each fitting, with the smaller diameter inner seal fitting inside the outer seal
- Seals are made of VO rated EPDM rubber
- The large diameter outer seal can be used alone on large cable but smaller diameter cable requires use of both clamping seals
- Seals can also be used with braided cables. Before mounting, fold the braid end over the clamping seal(s)
- The extra-robust counter nut provides increased clamping strength
- Secure the fitting to a box using the sealing ring and galvanized steel lock nut

### SPECIFICATIONS

- Stainless steel gland, male, consisting of four parts (body, counter nut and inner and outer (two-part) clamping seals)
- Body and counter nut are stainless steel AISI-316, inner and outer clamping seals are EPDM rubber
- Color: Metallic
- Temp. range: -49° F to +221° F (-45° C to +105° C)


### APPLICATIONS

- Relieve strain on Cat5e cable and wiring
- Connect capillary armor or MTC
- Put continuous conduit through walls
- Cleanly connect Greenfield without a clamshell
- Versatile grip ranges from a double seal

## STAINLESS STEEL AISI-316



Thread NPT (inches)	Item ID	UL/CSA* Both Seals Min. Diameter	Clamping Range Diameter (inches)		Dimensions (inches)				Weight (lbs/100)	Std. Pkg.
			Both Seals	Outer Seal	A	B	C	E		
1/2	73871292	0.216	0.157 - 0.256	0.256 - 0.335	1.417	0.551	0.669	0.945	10.1	10
1/2	73871692	0.295	0.236 - 0.354	0.354 - 0.472	1.535	0.551	0.866	0.945	11.2	10
3/4	73871892	0.295	0.236 - 0.354	0.354 - 0.472	1.575	0.551	0.866	1.181	15.0	5
3/4	73872092	0.472	0.413 - 0.551	0.551 - 0.669	1.654	0.551	1.063	1.181	16.1	5
1	73872392	0.472	0.413 - 0.551	0.551 - 0.669	1.732	0.630	1.063	1.496	24.0	5
1	73872692	0.669	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.496	26.0	5
1-1/4	73873092	0.669	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.890	38.6	2
1-1/4	73873592	0.925	0.866 - 1.063	1.063 - 1.220	1.890	0.630	1.693	1.890	40.8	2
1-1/2	73873892	0.925	0.866 - 1.063	1.063 - 1.220	1.969	0.709	1.693	2.165	51.8	2
1-1/2	73874092	1.20	1.161 - 1.378	1.378 - 1.575	2.520	0.709	2.087	2.165	66.1	2



## NICKEL-PLATED BRASS

Thread NPT (inches)	Item ID	UL/CSA* Both Seals Min. Diameter	Clamping Range Diameter (inches)		Dimensions (inches)				Weight (lbs/100)	Std. Pkg.
			Both Seals	Outer Seal	A	B	C	E		
1/2	7387122	0.216	0.157 - 0.256	0.256 - 0.335	1.417	0.551	0.669	0.945	10.1	10
1/2	7387162	0.295	0.236 - 0.354	0.354 - 0.472	1.535	0.551	0.866	0.945	11.2	10
3/4	7387182	0.295	0.236 - 0.354	0.354 - 0.472	1.575	0.551	0.866	1.181	15.0	5
3/4	7387202	0.472	0.413 - 0.551	0.551 - 0.669	1.654	0.551	1.063	1.181	16.1	5
1	7387232	0.472	0.413 - 0.551	0.551 - 0.669	1.732	0.630	1.063	1.496	24.0	5
1	7387262	0.669	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.496	26.0	5
1-1/4	7387302	0.669	0.61 - 0.787	0.787 - 0.945	1.811	0.630	1.378	1.890	38.6	2
1-1/4	7387352	0.925	0.866 - 1.063	1.063 - 1.220	1.890	0.630	1.693	1.890	40.8	2
1-1/2	7387382	0.925	0.866 - 1.063	1.063 - 1.220	1.969	0.709	1.693	2.165	51.8	2
1-1/2	7387402	1.20	1.161 - 1.378	1.378 - 1.575	2.520	0.709	2.087	2.165	66.1	2

\*For UL/CSA pull out strength of 36 lbs., the minimum diameter has been calculated for both seals by adding .059 inch to the normal minimum clamping diameter.