

Flexible Robot Conduit

ANAMET Industrial Solutions

Conduit and fittings protect wiring
and optical fiber from

- Intrusion and data breach
- Contamination
- Stress and strain
- Moving parts
- Corrosion

**TO
CONNECT
AND
PROTECT**

PHONE: (800) 230-3718
ANAMETINDUSTRIALSOLUTIONS.COM
INFO@ANAMETINDUSTRIALSOLUTIONS.COM

ANAMET INDUSTRIAL SOLUTIONS
ANACONDA SEALTITE®



MTC 3/8 to 2 inch diameter Machine Tool Extra Flexible Conduit


SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Black
- Temperature range: -4°F to +140°F (-20°C to +60°C)
- UV (sunlight) and corrosion resistant
- Tight bend radius

APPLICATIONS

- Armor casing for flexible drive shafts
- High flexibility
- Machine tool industry
- Power connection for distributed power systems

CW-BLUE 1/2 to 3 inch diameter

Computer flexible conduit 

SPECIFICATIONS

- Uses standard liquid tight connectors
- UL Listed and CSA Approved
- Color: Blue
- Temperature range: -40°F to +176°F (-40°C to +80°C)

APPLICATIONS

- Protect cable and wiring in data centers
- Approved for direct burial and in concrete at trade sizes 1/2"-3"
- Approved for use in cable raceways and under raised floors

UA 3/8 to 4 inch diameter Flexible metallic conduit



SPECIFICATIONS

- Uses standard liquid tight connectors
- Color: Pantone Matching System colors
- UL Listed and CSA Approved
- UL certified for temperature range -40°F to +176°F (-40°C to +80°C).
- CSA certified for 60°C dry / 60°C oil.


APPLICATIONS

- Protect cable and wiring in data centers
- Approved for direct burial and in concrete at trade sizes 1/2"-3"

1-800-230-3718 info@anametindustrialsolutions.com
www.anametindustrialsolutions.com

ANACONDA SEALTITE®

CNP

3/8 to 2 inch diameter 
Type A Non-metallic Flexible Conduit

SPECIFICATIONS

- Smooth inner PVC core with outer oil resistant PVC cover bonded with nylon reinforcing braid
- Temperature range: -4°F to +140°F (-20°C to 60°C)
- Color: Orange or Gray
- UV (sunlight) resistant, Flame retardant
- Oil resistant
- UL Listed and CSA Approved

APPLICATIONS

- Machine applications where non-metallic and flexing required
- Compact Type A SEALTITE® LFNC fittings available

SHIELDTITE® MIL

3/8 to 3 inch diameter
EMI/EMP resistant Zero Halogen, Low smoke

SPECIFICATIONS

- Bronze core with liquid tight TPU jacket
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) and corrosion resistant
- Special bronze core provides high-level shielding protection
- Meets MIL-STD-1310H
- Provides shielding effectiveness of 81-119 Db at 1 Mhz to 1 Ghz
- Meets MIL-STD-167/1, MILITARY STANDARD: MECHANICAL VIBRATIONS OF SHIPBOARD EQUIPMENT (TYPE I-ENVIRONMENTAL)
- Meets MIL-PRF-24758A(SH) when connected using SEALTITE® AISI-316 Halogen Free fittings

APPLICATIONS

- Military, power generation and communications



RoHS WEEE
Compliant



ANAMET INDUSTRIAL SOLUTIONS
ANACONDA SEALTITE®

