

SLB SS BRAIDED MULTIFLEX

STAINLESS STEEL MULTIFLEX SLB FLEXIBLE STAINLESS STEEL CAPILLARY ARMOR WITH STAINLESS STEEL WIRE BRAID

SLB



DESCRIPTION

- Flexible Stainless Steel conduit with a protective stainless steel wire braid cover
- Designed for OEM applications where corrosion is an issue and no approvals are required
- Designed to provide mechanical and EMC protection in critical applications
- This robust, stainless steel braid cover provides a high level of electromagnetic shielding for cables
- Typical applications include the steel, foundry, metalworking and other demanding heavy duty industries
- Additional Put-ups available

SPECIFICATIONS

- Type 304 stainless steel square lock capillary armor with braid (SLB)
- Temperature: +450°F (+232°C) max.

APPLICATIONS

- Applications where corrosion is an issue and where no approvals are required
- Sensor cable protection
- OEM probe cables
- Optical fiber
- Instrumentation
- Temperature measuring devices



Square locked



Trade Size (inches)	Item ID	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius		Small Carton Feet	Weight lbs/100 ft
		Min	Max	Static (in)	Dynamic (in)				
5/16	107.710.2	0.390	0.531	1.456	2.0	98	35		
3/8	107.712.2	0.485	0.622	1.771	2.3	98	41		
1/2	107.716.2	0.620	0.807	2.165	3.2	98	55		
3/4	107.720.2	0.815	1.000	2.756	4.0	98	75		
1	107.726.2	1.030	1.291	3.740	5.0	98	141		
1-1/4	107.735.2	1.370	1.595	4.523	6.3	98	207		
1-1/2	107.740.2	1.575	1.831	6.500	9.8	49	269		
2	107.750.2	2.020	2.283	8.268	11.8	49	399		