

# SLI MULTIFLEX

## 316 STAINLESS STEEL SL MULTIFLEX CONDUIT



### DESCRIPTION

- Ultra flexible galvanized steel conduit
- Designed for OEM applications where high flexibility but no approvals are required
- Installs easily using standard armored or flexible conduit connectors

### SPECIFICATIONS

- Constructed of continuously interlocked stainless steel core for exceptional crush and corrosion resistance
- Temperature: +450°F (+232°C) max.
- Exceptional flexibility for tight "U" bend radius

### APPLICATIONS

- OEM applications where tight bend radius is required, but no approvals are required
- Steel and iron foundries
- Marine and ship building
- Machine building



Square-Locked Design



Trade Size (inches)	Item ID	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)
		Min	Max	Min	Max		
3/8	426008	0.484	0.504	0.600	0.620	2.5	13.1
1/2	426009	0.620	0.640	0.735	0.755	2.5	16.4
3/4	426019	0.815	0.835	0.930	0.950	3.0	22.3
1	426029	1.030	1.055	1.170	1.195	4.0	31.2
1-1/4	426039	1.370	1.395	1.510	1.535	4.5	40.6
1-1/2	426049	1.575	1.600	1.725	1.750	5.5	62.6
2	426059	2.020	2.045	2.170	2.195	7.0	79.4